

VACUUM SYSTEM FOR STEEL DUSTS

ADVANTAGES

- Modular system modular construction to meet higher operational or legal requirements can be retrofitted at any time without problems
- No need to buy expensive filter bags all the time
- · Convenient and quick foot lever emptying

APPROVED UTILISATION

- Combustible as well as non-combustible dust with exposure limits* ≥ 0.1 mg/m³ with recirculation of clean air into the work area
- **Dust class M** (including dust class L)

* AGW- Occupational exposure limit value

SCOPE OF DELIVERY

- 1 × mobile vacuum unit with grey hood filter class M | zone 22 | CE 400V 16A
- 1 × hose plastic Ø 50 mm l 5 m with Storz C clutch
- 1 × hose plastic Ø 40 mm | 5 m with Storz C clutch
- 1 \times plastic hose Ø 50 mm l 5 m with pressure pin

- ltem no. 881089
- $1 \times \text{transition} \emptyset 50 \text{ mm}$ Storz C clutch to pressure pin
- 1 x curved hand tube Ø 50 mm
- $1 \times \text{hand tube stainless steel } \emptyset 50 \text{ mm} | 1 \text{ m}$
- 1 × floor nozzle cast aluminum body | 50 cm wide
- 1 × crevice nozzle | 30 cm long
- 1 x holder suction arm